

10/661,841

## 1. (CURRENTLY AMENDED) A chemical toilet comprising:

a housing having an aperture therein providing access to an interior compartment of the housing, and the interior compartment of the housing having a toilet with a toilet opening directly communicating with a storage tank; and

an exterior wall of the housing having a wall pumping coupling and a lower most portion of the storage tank having a tank pumping coupling and the wall pumping coupling and the tank pumping coupling[[s]] being interconnected with one another by a pumping conduit to facilitate pumping of human waste and liquid from the storage tank via the pumping conduit during servicing of the chemical toilet by a service vehicle, a base surface of the storage tank being inclined and an inlet, defined by the tank pumping coupling, and the inlet being fixed located in the lower adjacent a lower most portion of the inclined base surface of the storage tank and in constant and continuous communication with to facilitate channeling and flow of any human waste and liquid contained within the storage tank such that any human waste and liquid contained within the storage tank is free to flow into the tank pumping coupling and a portion of the pumping conduit during servicing of the chemical toilet.

2. (CURRENTLY AMENDED) The chemical toilet according to claim 1, wherein the wall pumping coupling is accommodated with a recess formed in the exterior wall of the housing and a fresh water recess supply coupling is also accommodated therein;

at least one spray nozzle is located within the storage tank and a fresh water conduit interconnects the recess supply coupling with the at least one spray nozzle to facilitate spraying of the interior of the storage tank during the pumping operation servicing of the chemical toilet.

3. (PREVIOUSLY PRESENTED) The chemical toilet according to claim 2, wherein a plurality of spray nozzles are located within the interior of the storage tank and the plurality of spray nozzles each spray a desired surface of the storage tank to facilitate cleansing thereof.

4. (PREVIOUSLY PRESENTED) The chemical toilet according to claim 3, wherein the plurality of spray nozzles are connected to one another by a common manifold.

5. (PREVIOUSLY PRESENTED) The chemical toilet according to claim 1, wherein the chemical toilet includes a pivotable seat and a pivotable lid, the seat and

11/18/05 12:25 PM

10/661,841

lid are both arranged to overlie the toilet opening, and lid is pivotable relative to the seat, and the wall pumping coupling being located horizontally above both the storage tank and the tank pumping coupling to prevent leakage of the human waste and liquid via the wall pumping coupling.

6. (PREVIOUSLY PRESENTED) The chemical toilet according to claim 1, wherein a urinal is accommodated within the interior compartment of the chemical toilet, and the urinal is coupled to the storage tank by a urinal drainage conduit to convey fluid from the urinal to the storage tank.

7. (WITHDRAWN - CURRENTLY AMENDED) The chemical toilet according to claim 1, wherein the storage tank has a base surface and the base surface is inclined and includes a trough, and the inclined base surface facilitates channeling of human waste and liquid into the trough, and the trough communicates with the inlet of the tank pumping coupling to facilitate flow and pumping of the human waste and liquid from the storage tank.

8. (WITHDRAWN - CURRENTLY AMENDED) The chemical toilet according to claim 7, wherein a shield is supported within the storage tank adjacent the trough and the shield restricts an undesired object from entering into the trough.

9. (WITHDRAWN - CURRENTLY AMENDED) The chemical toilet according to claim 8, wherein the shield is attached to a side wall of the storage tank and located above the trough, and the shield is spaced from the base ~~[[wall]]~~ surface by a distance of between ½ inch to 2 inches.

10. (WITHDRAWN - CURRENTLY AMENDED) The chemical toilet according to claim 1, wherein the trough has one of a screen and a grating for restricting an undesired object from entering into the trough.

11. (WITHDRAWN - CURRENTLY AMENDED) The chemical toilet according to claim 1, wherein the storage tank has a funnel shaped inclined base surface with a drain formed therein;

the funnel shaped inclined base surface facilitates channeling of human waste and liquid into the drain; and

the drain communicates with the inlet of the tank pumping coupling to facilitate pumping of the human waste and liquid from the storage tank.

11/18/05 1:22 PM

10/661,841

12. (CURRENTLY AMENDED) The chemical toilet according to claim 11, wherein the drain has one of a screen and a grating for restricting an undesired object from entering into the drain. ♦♦

13. (PREVIOUSLY PRESENTED) The chemical toilet according to claim 1, wherein the housing of the chemical toilet is enclosed and has four side wall and a roof, and a door is located to close the aperture providing access to the interior compartment of the housing.

14. (PREVIOUSLY PRESENTED) The chemical toilet according to claim 13, wherein a vent extends through an upper region of the chemical toilet and the vent is coupled to the storage tank to facilitate venting of noxious odors from the storage tank to an exterior of the chemical toilet.

15. (WITHDRAWN - CURRENTLY AMENDED) The chemical toilet according to claim 2, wherein the service vehicle has a fresh water supply source and a collection reservoir for collecting human waste removed from the storage tank;

the fresh water supply source includes a pumping device for pumping fresh water from the fresh water supply source along a flexible fresh water hose to a fresh water ball valve, and the fresh water ball valve is connectable to the fresh water supply coupling; and ♦♦

the collection reservoir includes a pumping device for pumping human waste from the storage tank and a flexible pump hose connected to a pump ball valve, and the pump ball valve is connectable with a pump coupling of the chemical toilet. ♦♦

16. (WITHDRAWN - CURRENTLY AMENDED) The chemical toilet according to claim 2, wherein the service vehicle has a fresh water supply source and a collection reservoir for collecting human waste removed from the storage tank;

the fresh water supply source includes a pumping device for pumping fresh water from the fresh water supply source along a flexible fresh water hose to a fresh water ball valve, and the fresh water ball valve is connectable to a spray hose with a quick connect coupling at one end thereof and a water nozzle at the opposite end thereof to facilitate spraying of the fresh water therefrom; and ♦♦

the collection reservoir includes a pumping device for pumping human waste from the storage tank and a flexible pump hose connected to a pump ball valve, the pump ball valve is connectable with a rigid section of pipe with a quick connect ♦♦

11/18/05 - 12:28 PM

10/661,841

coupling at one end thereof and an inlet at the opposite end thereof to facilitate pumping of fluid and human waste therefrom.

17. (CURRENTLY AMENDED) A chemical toilet comprising:

a housing accommodating a toilet therein and the toilet having an opening directly communicating with a storage tank; and

an exterior wall of the housing having a wall pumping coupling and a lower portion of the storage tank having a tank pumping coupling with an inlet and the wall pumping coupling and the tank pumping coupling[[s]] being interconnected with one another by a pumping conduit to facilitate pumping of human waste from the storage tank during servicing of the chemical toilet by a service vehicle, a base surface of the storage tank being inclined with an inlet, defined by the tank pumping coupling, being fixedly located adjacent a lower most portion of the inclined base surface of the storage tank to facilitate channeling and flow of any human waste and liquid contained within the storage tank into the tank pumping coupling during servicing of the chemical toilet;

the inlet of the tank pumping coupling being permanently located adjacent the lower most portion of the storage tank, and the wall pumping coupling being located horizontally above both the storage tank and the tank pumping coupling to prevent leakage of the human waste and liquid via the wall pumping coupling.

18. (CURRENTLY AMENDED) The chemical toilet according to claim 17, wherein at least one spray nozzle is located within the storage tank and a fresh water conduit interconnects the at least one spray nozzle with a source of fresh water to facilitate spraying of an interior of the storage tank during [[the]] pumping of human waste from the storage tank while servicing of the chemical toilet.

19-20. (CANCELED)

21. (CURRENTLY AMENDED) A method of producing a chemical toilet comprising:

forming an aperture in a housing to provide access to an interior compartment of the housing, and the interior compartment of the housing having a toilet with an opening directly communicating with a storage tank; and

locating a wall pumping coupling on an exterior wall of the housing and interconnecting a tank pumping coupling, located in a vertically lower most portion of the storage tank, with the wall pumping coupling by a pumping conduit to facilitate

11/18/05 12:33 PM

10/661,841

pumping of human waste and liquid from the storage tank via the pumping conduit during servicing of the chemical toilet by a service vehicle, a base surface of the storage tank being inclined and an inlet, defined by the tank pumping coupling, with the inlet being fixedly located in the lower adjacent the vertically lower most portion of the inclined storage tank and in constant and continuous communication with to facilitate channeling and flow of any human waste and liquid contained within the storage tank such that any human waste and liquid contained within the storage tank is free to flow into the tank pumping coupling and a portion of the pumping conduit during servicing of the chemical toilet, and the wall pumping coupling being located horizontally above the storage tank and the tank pumping coupling to prevent leakage of the human waste and liquid. ◆◆

22. (CURRENTLY AMENDED) The method according to claim 21, further comprising the step of supplying water to the storage tank, simultaneously while pumping human waste from the storage tank, to facilitate flushing cleaning of the storage tank during servicing of the chemical toilet. ◆◆